

ARTIFACT SHEET

Enter artifact number below. Artifact number is application number + artifact type code (see list below) + sequential letter (A, B, C ...). The first artifact folder for an artifact type receives the letter A, the second B, etc..

Examples: 59123456PA, 59123456PB, 59123456ZA, 59123456ZB

09/067826 BA

Indicate quantity of a single type of artifact received but not scanned. Create individual artifact folder/box and artifact number for each Artifact Type.

☐

CD(s) containing:

computer program listing

Doc Code: Computer

pages of specification

and/or sequence listing

and/or table

Doc Code: Artifact

content unspecified or combined

Doc Code: Artifact

☐

Artifact Type Code: P

☐

Artifact Type Code: S

☐

Artifact Type Code: U

☐

Stapled Set(s) Color Documents or B/W Photographs

Doc Code: Artifact

Artifact Type Code: C

☐

Microfilm(s)

Doc Code: Artifact

Artifact Type Code: F

☐

Video tape(s)

Doc Code: Artifact

Artifact Type Code: V

☐

Model(s)

Doc Code: Artifact

Artifact Type Code: M

☒

Bound Document(s)

Doc Code: Artifact

Artifact Type Code: B

☐

Confidential Information Disclosure Statement or Other Documents marked Proprietary, Trade Secrets, Subject to Protective Order, Material Submitted under MPEP 724.02, etc.

Doc Code: Artifact

Artifact Type Code X

☐

Other, description: _____

Doc Code: Artifact

Artifact Type Code: Z

The United States of America



The Commissioner of Patents and Trademarks

Has received an application for a patent for a new and useful invention. The title and description of the invention are enclosed. The requirements of law have been complied with, and it has been determined that a patent on the invention shall be granted under the law.

Therefore, this

United States Patent

Grants to the person(s) having title to this patent the right to exclude others from making, using, offering for sale, or selling the invention throughout the United States of America or importing the invention into the United States of America for the term set forth below, subject to the payment of maintenance fees as provided by law.

If this application was filed prior to June 8, 1995, the term of this patent is the longer of seventeen years from the date of grant of this patent or twenty years from the earliest effective U.S. filing date of the application, subject to any statutory extension.

If this application was filed on or after June 8, 1995, the term of this patent is twenty years from the U.S. filing date, subject to any statutory extension. If the application contains a specific reference to an earlier filed application or applications under 35 U.S.C. 120, 121 or 365(c), the term of the patent is twenty years from the date on which the earliest application was filed, subject to any statutory extension.

Bence Lehman

Commissioner of Patents and Trademarks

Attest

Mary H. Queen

U.S. PTO
09/667826
09/21/00



US005811808A

United States Patent [19]

Cannata et al.

[11] Patent Number: **5,811,808**[45] Date of Patent: **Sep. 22, 1998****[54] INFRARED IMAGING SYSTEM
EMPLOYING ON-FOCAL PLANE
NONUNIFORMITY CORRECTION**

[75] Inventors: **Robert F. Cannata**, Santa Barbara,
Calif.; **Jeffrey L. Metschuleit**,
Fisherville, Ky.

[73] Assignee: **Amber Engineering, Inc.**, Goleta,
Calif.

[21] Appl. No.: **712,891**

[22] Filed: **Sep. 12, 1996**

[51] Int. Cl.⁶ **G01J 5/20; G01J 5/24**

[52] U.S. Cl. **250/332; 250/349; 250/370.08**

[58] Field of Search **250/332, 349,
250/338.4, 370.08**

[56] References Cited**U.S. PATENT DOCUMENTS**

4,719,512 1/1988 Endo et al. .
4,752,694 6/1988 Hegel, Jr. et al. .
4,771,267 9/1988 Russell, Jr. et al. .
4,903,144 2/1990 Stefanik et al. .
4,953,028 8/1990 Murayama et al. .
4,987,294 1/1991 Romer .
5,157,500 10/1992 Gusmano .
5,159,457 10/1992 Kawabata .
5,162,912 11/1992 Ueno et al. .

5,182,446 1/1993 Tew .
5,286,976 2/1994 Cole .
5,300,915 4/1994 Higashi et al. .
5,489,776 2/1996 Lung' 250/332
5,528,035 6/1996 Masarik et al. 250/332

FOREIGN PATENT DOCUMENTS

5-264357 10/1993 Japan 250/332

Primary Examiner—Edward J. Glick

Attorney, Agent, or Firm—Graham & James LLP

[57] ABSTRACT

An infrared imaging system having a focal plane array including an array of detector elements and a readout circuit and including nonuniformity correction circuitry on the focal plane array. The individual detector elements correspond to pixels of an infrared scene to be imaged. Offsets in detection signals from each pixel arising from nonuniformities in the individual detector elements in the array are corrected by storing offset correction values for each detector element and using the stored offset values to control correction circuitry as the respective detector element signals are read out. The detector array and readout circuit are preferably formed as a monolithic or hybrid structure and the offset correction is provided on the focal plane array prior to signal amplification and analog to digital conversion.

35 Claims, 10 Drawing Sheets